

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4675)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
An X cut on a rock bears S.41°W., 20 lks.
An X cut on a rock bears N.45°W., 14 lks.
Impossible to dig pit.
No trees within limits to mark as BT.

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4717)

Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:
The ¼ sec. cor. which is as described in original notes and from which a cross (X) cut in rock, bears N.45°W., 14 lks.
A fir, 8" dia., bears S.75°E., 66 lks., marked ¼ S BT.

Triangle Engineering Co. Nick Juliano - May 1972 - M44-79 & C.S. File 55/251

No evidence found of "X" on rocks or of 8" BT.
Set - 1½" IP with brass cap. Referenced with "W" nails & plates.
New - 16" Fir, N.43½°W., 3.6 ft.
20" Fir, S.01°W., 25.0 ft.

Fd. Ok 8/1985 - Michael McDowell, Weyerhaeuser. M99-18