

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; & 2, 3, T27-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4642)

- 
- Cor. to secs.2, 3, 34 and 35, from which
- A Hemlock 10" dia., bears N.60°E., 29 lks. dist.
  - A Hemlock 24" dia., bears N.60°W., 24 lks. dist.
  - A Fir 36" dia., bears S.25°E., 64 lks. dist.
  - A Yew 6" dia., bears S.10°W., 44 lks. dist.

Craig L. Templin - For: Weyerhaeuser Co. - March 22, 1973 - C.S. File 55/285C (added 2/5/2008)

- 
- NW cor. sec. 2: An iron pipe, from which
- 8" fir bears N.58°E. 18.6 ft (Weyco tag, W nail & scribed)
  - 10" fir bears N.68°W., 13.1 ft. (Weyco tag, W nail & scribed)
  - 8" madrone bears S.87°W., 17.6 ft. (Weyco tag, W nail & scribed)
  - 8" hemlock bears S.77°E., 10.7 ft. (Weyco tag, W nail & scribed)

Shaner Engineering - For: Hub Lumber Co. - June 24, 1974 - RM 2-63

- 
- Found 1½" I.P. and SET brass cap alongside mkd. "T26S R8W WM S34 S35 T27S R8W S3 S2 1974", from which found
- 60" Orig. D.Fir BT stump, with partial face, bears S.25°E., 42.2 ft.
  - 6" Yew, possible BT, down and rotting, bears S.10°W., 29.0 ft.
  - 36" D.Fir stump scribed visible, bears S.81°E., 36.5 ft.
  - 8" D.Fir BT, no scribes on face, I scribed "T26S R8W S35 BT", bears N.58°E., 18.6 ft.
  - 10" D.Fir BT faced but no scribes vis., I scribed "T26S R8W S34 BT", bears N.68°W., 13.1 ft.
  - 8" Madrone BT bark scribes visible, bears S.87°W., 17.6'
  - 8" Hemlock BT, faced but no scribes, I scribed "T27S R8W S2 BT", bears S.77°E., 10.7 ft.
- Badly burned post with scribes visible wired to pipe.  
Last 4 trees have "Weyco" tags and "W" nails in root collars.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; & 2, 3, T27-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM resurvey by Harvey E. Wofford & John P. Farnsworth, Cadastral Surveyors, under Group #'s 981 & 1065, Surveyed May 30, 1979/July 20, 1981 - (DCSO records Vol 44 Pages 17041-42)

The Sec. Cor., perpetuated and recorded by Shaner, monumented with an iron post, 1½" dia., with a brass cap firmly set, projecting 7" above ground, alongside of which is an iron

A Fir stump 60" dia., bears S.25°E., 71 lks. dist., with old axe marks visible on decayed blaze. (Rec. 64 lks.)

A root hole bears S.10°W., 44 lks. dist., alongside of which is a downed decayed Yew, 6" dia., with no marks remaining.

and trees mkd. by person(s) unknown

A Fir 10" dia., bears N.61°E., 28½ lks. dist., with healed blaze.

A Fir stump 36" dia., bears S.81°E., 57 lks. dist., with healed blaze.

A Hemlock snag 8" dia., bears S.77°E., 16½ lks. dist., remarked S2 T27S R8W BT by Shaner.

A twin Madrone 8" dia., bears S.87°W., 26½ lks. dist., with illegible scribe marks visible on bark blaze.

A Fir 23" dia., bears N.68°W., 19½ lks. dist., with healed blaze.

and a new bearing tree

A Fir 13" dia., bears S.66½°E., 22 lks. dist. mkd. T27S R8W S2 BT.