

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4662)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which

 A fir, 40" dia., bears N.22°E., 220 lks., mkd: ¼ S BT.

 A fir, 36" dia., bears N.55°W., 240 lks., mkd: ¼ S BT.

Bruce Shaner - For: Hub Lumber Co. - M49-33 - Aug. 16, 1973

Found - 52" Orig. D.Fir opened face & found scribe "1". Face burned & axe marks vis. Rescribed "¼ S34 BT" bears N.55°W., 158.4 ft. (Record 36")

Set - Brass cap mkd. T26S R8W, ¼ S34, S35 1973.

New BTs- 12" D.Fir, scribed "¼ S35 BT" bears N.44°E., 15.0 ft

 10" D.Fir, Scribed "¼ S34 BT" bears S.53°W., 5.9 ft

Fd. Ok by Ken Hoffine (painted faces & wrote BT on tree trunks of all BTs with flour. orange paint) 3/1990 C.S. File 63/104-64