

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4662)</p> <p>-----</p> <p>Set a yew post, 3 ft. long, 4" sq., with charred stake, 24" in the ground for cor. of sec. 26, 27, 34, & 35, mkd T26S S26 on NE, R8W S35 on SE, S34 on SW & S27 on NW faces with 1 notch on S and 2 notches on E edges, and dug pits 18x18x12" in each sec. 5½ ft. dist. & raised a mound of earth 4 ft. base, 2 ft. high W of cor. No living trees within limits.</p>
<p>GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4715)</p> <p>-----</p> <p>Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898: The Cor. to secs. 26, 27, 34 and 35, as described by the Examiner, I inscribe the omitted markings thereon Viz:T26S on NE, R8W on SE. and 1 notch on S and 2 notches on E edges; dig pits 18x18x12", in each Sec. 5½ ft. distant and raised mound of earth 4 ft. base, 2 ft. high, W. of Cor.</p>
<p>Bruce Shaner - For: Hub Lumber Co. - M49-33 - Aug. 16, 1973</p> <p>-----</p> <p>Set - Brass cap mkd. T26S R8W WM S27 S26 S34, S35, 1973 New - 12" D.Fir, scribed "T26S R8W S27 BT bears N.84°W, 27.4 ft. 10" D.Fir, scribed "T26S, R8W, S26 BT" bears N.43°E., 32.1 ft. 10" D.Fir, scribed "T26S, R8W, S34 BT" bears S.61°W., 40.9 ft. 10" D.Fir, scribed "T26S, R8W, S35 BT" bears S.67½°E., 10.3 ft.</p>
<p>Fd. Ok 7/1990 - C.S. File 63/127-31</p>
<p>1</p>