

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4666)

-----

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 14, 15, 22, & 23, 30 ft. below the level ground mkd T26S S14 on NE, R8W S23 on SE, S22 on SW & S15 on NW faces with 3 notches on S & 2 notches on E edges, from which  
A fir, 18" dia. bears N.41°E. 38 lks. mkd: T26S R8W S14 BT  
A W.Fir, 18" dia., bears S.25°E., 46 lks., mkd: T26S R8W S23 BT.  
A fir, 12" dia. bears S.51°W. 42 lks. mkd: T26S R8W S22 BT  
A fir, 12" dia., bears N.22½°W., 66 lks., mkd: T26S R8W S15 BT.

Triangle Engineering Co. Nick Juliano - May 1972 - M44-79 & C.S. File 55/251

-----

Found - 24" Fir, N.41°E., 25.1 ft. Scar visible.  
Rotted Stump, S.25°E., 30.4 ft.  
20" Fir, Downed, S.51°W., 27.7 ft. Scar visible.  
16" Fir, Downed, N.22½°W., 43.6 ft. Scar visible.  
Set - 1½" Iron pipe with brass cap. Referenced with "W" nails and plates.  
New BTs- 8" Hemlock, S.15°W., 26.1 ft.  
16" Hemlock, S.63°E., 19.5 ft.  
8" Hemlock, N.61°W., 30.7 ft.