

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4668)

-----

Set cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 10, 11, 14, & 15, mkd T26S S11 on NE, R8W S14 on SE, S15 on SW & S10 on NW faces with 4 notches on S and 2 notches on E edges, from which

- A fir, 24" dia bears N.82°E. 171 lks. mkd: T26S R8W S11 BT
- A fir, 4" dia. bears S.18°E. 197 lks. mkd: T26S R8W S14 BT
- A fir, 36" dia. bears S.2°W. 250 lks. mkd: T26S R8W S15 BT
- A fir, 18" dia. bears N.5°W. 275 lks. mkd: T26S R8W S10 BT

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #350, surveyed May 1977 - (DCSO records Vol. 40 Page(s) 15952)

-----

The cor. of sees. 10, 11, 14, & 15, determined at record distance from the remaining orig BTs:

- A fir, 52" dia., bears S.86½°E., 171 lks., with scribe marks BT visible on bark blaze. (Record, N.82°E.)
- A fir, 55" dia., bears S.12°E., 197 lks., with scribe marks T S W BT visible on bark blaze. (Record, S.18°E.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T26S R8W  
S 10|S 11  
S 15|S 14  
1977

from which new BTs

- A fir, 15" dia., bears N.48¾°E., 48 lks., mkd: T26S R8W S11 BT.
- A hemlock, 11" dia., bears S.17°W., 30 lks., mkd: T26S R8W S15 BT.
- A fir, 21" dia., bears N.80°W., 14½ lks., mkd: T26S R8W S10 BT.