

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4669-70)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 2, 3, 10, & 11, mkd T26S S2 on NE, R8W S11 on SE, S10 on SW & S3 on NW faces with 5 notches on S and 2 notches on E edges, from which
A fir, 36" dia. bears N.22°E. 116 lks. mkd: T26S R8W S2 BT
A fir, 30" dia., bears S.17°E., 115 lks., mkd: T26S R8W S11 BT.
A fir, 18" dia., bears S.73°W., 244 lks., mkd: T26S R8W S10 BT.
A fir, 24" dia., bears N.28°W., 105 lks., mkd: T26S R8W S3 BT.

Weyerhaeuser reports received 6/17/1970 - C.S. File 55/155A

By Lester Minister, 11/1968 fd. 4 BTs & mks.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #350, surveyed May 1977 - (DCSO records Vol. 40 Page(s) 15952-3)

The cor., of secs. 2, 3, 10, & 11, determined from the OBTs:
A fir, 52" dia., bears N.17°E., 103 lks., with fragmentary scribe marks visible on weathered bark blaze. (Record, N.22°E., 116 lks., distance on slope.)
A fir, 45" dia., bears S.9°E., 101 lks., no marks visible on weathered bark blaze. (Record, S.17°E., 115 lks.)
A fir, 28" dia., bears S.73°W., 216 lks., with scribe marks BT visible on bark blaze. (Record, 244 lks., & distance on slope.)
A fir, 30" dia., bears N.35¼°W., 86½ lks., with scribe marks T 2 R BT visible on bark blaze. (Record, N.28°W., 105 lks., and distance on slope.)

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:
T26S R8W
S 3|S 2
S 10|S 11
1977

from which new BTs
A fir, 12" dia. bears N.8°E., 23½ lks. mkd: T26S R8W S2 BT
A fir, 18" dia. bears S.28°E., 6 lks. mkd: T26S R8W S11 BT
A fir, 13" dia. bears N.88°W., 29 lks. mkd: T26S R8W S3 BT