

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A. R. and S.C. Flint, Under Contract #392,
dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3931)

Cor. to secs. 2, 3, 34 and 35, on steep ridge NW. & SE. Set
a Fir post 4 ft. long, 4" dia., firmly in the ground, form
which

A Fir 15" dia., bears N.75°E., 13 lks. dist.

A Fir 60" dia., bears S.20°W., 65 lks. dist.

A Fir 15" dia., bears S.40°E., 68 lks. dist.

A Cedar 18" dia., bears N.45°W., 65 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
July 25, 1968 - C.S. File 54/72-5

Found - Orig. 15" now 36" Fir, alive, N.75°E., 8.6 ft., bark
scribe in poor condition.

Orig. 18" now 24" Cedar, alive, N.45°W., 42.9 ft.,
shows good scar.

Orig. 60" now 72" Fir, alive, S.20°W., 42.9 ft., no
scribe or scar.

Set Brass cap at cor. mkd: County Surveyors Office

T25S R8W S 34 | S 35
T26S S 31 S 2

1968

New BTs- 10" D.Fir N.42°W., 34.3 ft. mkd. T25S R8W S34 CS BT

10" D.Fir N.41°E., 6.7 ft. mkd. T25S R8W S35 CS BT.

5" D.Fir S.25°E., 18.5 ft. mkd. S2 CS BT.

11" Maple S.6°W., 15.0 ft. mkd. T26S R8W S3 CS BT.

Corner lies on very steep Sw. slope about 165 ft. E. of cree,
course NW.