

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4663)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which

 A fir, 3" dia., bears N.8°W., 150 lks., mkd: ¼ S BT.

 A fir, 48" dia., bears S.38°W., 127 lks., mkd: ¼ S BT.

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4715)

Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:

The ¼ sec. cor. which I find as reported in the notes now on file in the US Surveyors General's Office.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Wit: J. D Kirklin & James Goodin - July 6-29, 1960 - C.S. File 51/116

Monumented with a yew wood post with partial scribe marks in a mound of stone. The orig BTs have been destroyed by fire. Set in place of the yew wood post an IP 3' long, 1½" dia. 28" In the ground, mkd. RS404 from which new BTs:

 20" D.Fir bears S.58°W., 13 lks. mkd. ¼ S35 RS404 BT

 22" D.Fir bears N.1°W., 64 lks. mkd. ¼ S26 RS404 BT

Fd. Ok 3/1990 C.S. File 63/127-24