

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4670-1)

-----  
Set fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which  
A fir, 18" dia., bears N.62°W., 32 lks., mkd: ¼ S BT.  
A fir, 36" dia., bears S.30°W., 60 lks., mkd: ¼ S BT.

-----  
Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15217)

-----  
The ¼ sec. cor. of secs. 2 & 11, determined at record bearing & distance, from the remains of the original bearing trees:  
A root hole, bears N.62° W., 32 lks., with a down fir snag alongside, 28" dia., no marks visible.  
A fir, 63" dia., bears S.30°W., 60 lks., with scribe marks S11 ¼ BT visible on bark blaze.

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.  
¼  $\frac{S \ 2}{S \ 11}$   
1971

from which a new bearing tree  
A hemlock, 10" dia., bears S.43°E., 57 lks., mkd. ¼ S11 BT