TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Corner Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Pg 4651)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 40" dia., bears S.3°45'E., 210 lks., mkd: ¼ S BT.
A fir, 36" dia., bears S.47°W., 129 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron - M Godfrey - C. Putnam - April 20, 1961 - C.S. File 52/79-3

Found - Orig. 40" now 44" Fir snag S.3°45'E., 138.6 ft., shows good scribing on old face "¼S"
Parts of old Fir stump that checks for orig. SW BT.
Note - Auto axle found bears S.49°W., 6.8 ft.
Set - Brass cap at cor mkd: County Surveyors Office 1961
¼ S35|S 36 T26S R8W
New BTs- 17" R.Fir bears S.42°W., 10.5 ft scribed ¼ S35 CS BT
15" R.Fir bears N.44°E., 31.0 ft scribed ¼ S36 CS BT

Ken Hoffine - For: Lone Rock Timber Co. - July 1990 - C.S. File 63/129-2

Corner report only
Found - Corner is a 1961 County brass cap 1.2 ft. above ground. 1961
27" D.Fir bears S.42°W., 10.5 ft. well healed face & 2 BT tags.
28" D.Fir bears N.44°E., 31.0 ft. well healed face & BT tags.
1" axle iron bears S.48°W., 6.9 ft.
Painted faces and wrote BT on tree trunks of BTs with florescent orange paint. Corner lies on East slope approx. 95 ft. east of flat bench.

Tony Hostetter - For: Weyerhaeuser Co - 6/2023 - C.S. 65/113-2

Found - 1961 DCSO (C.S. 52/79-3)
18" Fir stump, face evident, BT Tag, bears S.42°W., 10.5 ft. to center.
50" Fir, face evident, bears N.44°E., 31.0 ft to center.
New BTs- 14" Fir, marked "X", BT tag, bears S.21°45'E., 13.7 ft to 6" spike, below "X"
10" Fir, marked "X", BT tag, bears N.15°36'W., 17.2 ft to 6" spike, below "X"
Note - Bearings on New BTs are based on 1973 Shaner survey M49-49