

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4653)

-----

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which

A fir, 6" dia., bears N.6°E., 36 lks., mkd: ¼ S BT.

A fir, 6" dia., bears N.20°W., 34 lks., mkd: ¼ S BT.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Wit: J. D Kirklin & James Goodin - July 6-29, 1960 - C.S. File 51/116

-----

Found - Determined from the only extant original bearing 14" D.Fir snag 6 ft tall bears N.20°W. 34 lks mkd BT

Set Iron pipe 3' long 1½" in dia., 28" in the ground mkd. RS404, from which new bearing trees:

10" Cedar bears S.8°E., 58 lks. mkd. ¼ S25 RS404 BT.

14" Hemlock bears N.6°W., 63 lks. mkd ¼ S26 RS404 BT

Fd. OK by B. Holt, 4/1981 - M87-55