TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4655)

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
A fir, 48" dia., bears N.20°E., 88 lks., mkd: ¼ S BT.
A maple, 5" dia., bears N.35°W., 14 lks., mkd: ¼ S BT.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15211)

The ¼ sec. cor. of secs. 23 & 24 determined at the record bearing & distance from the remains of the orig. BTs.
A fir, 50" dia., bears N.20°E., 88 lks. with healed blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼
S 23|S 24
T26S R8W
1971

from which new BTs:
An Alder, 5" dia., bears S.88°E., 31 lks., mkd: ¼ S24 BT.
A fir, 16" dia., bears N.29°W., 49 lks., mkd: ¼ S23 BT.

Tony Hostetter, surveyed for Weyerhaeuser Co. Nov. 1998 - M131-5

Found - 1971 BLM brass cap as described in Vol. 37 Pg. 15211
40" Fir stump, Weyco tag & "W" nail, bears N.20°E., 57.2 ft.
16" Fir stump, face evident, BT tag, bears N.29½°W., 31.9 ft.
New - 12" Alder, bark scribed "S24 ¼ BT" bears N.64°E., 24.1 ft.
16" Hemlock scribed "S24 ¼ BT" bears S.65°E. 43.7 ft
10" Alder bark scribed "S23 ¼ BT" bears S.7°W 1.2 ft
Note - Measured dist to new accessories is to 6" spike in root collar (below face).