TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4661)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which

A fir, 8" dia., bears N.48°E., 16 lks., mkd: ¼ S BT.
A hemlock, 8" dia., bears N.33°W., 46 lks., mkd: ¼ S BT.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15217-8)

The ¼ sec. cor. of secs. 11 & 12, determined at record bearing & distance from the remains of the orig. BTs:

A sawed fir stump, 50" dia., bears N.48°E., 16 lks., with fragmentary scribe marks visible on opened & decayed blaze.
A root hole, bears N.33° W., 46 lks.

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼
S 11|S 12
T26S R8W
1971

from which new BTs

A fir, 7" dia., bears N.86°E., 27 lks., mkd: ¼ S12 BT.
A fir, 13" dia., bears N.49°W., 41½ lks., mkd: ¼ S11 BT.

BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1128 surveyed Jan. 1983- (DCSO records Vol. 43 Page(s) 16754)

Beginning at the ¼ sec. cor. of secs. 11 & 12, monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Peterson & Berry

A root hole, bears N.86°E., 27.0 lks., with down fir alongside, 12 ins. diam., with healed blaze.

A sawed fir stump, 16" dia., bears N.49°W., 41½ lks., with scribe marks ¼ S11 visible on partially healed blaze.

and new bearing trees

A fir, 6" dia., bears N.88°E., 7½ lks., mkd. ¼ S12 BT.
A fir, 5" dia., bears S.28¾°W., 42 lks., mkd. ¼ S11 BT.