

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Closing corner Secs 11 & 12 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4648)

Cor. to secs. 1, 2, 11, & 12, from which
A fir, 48" dia., bears S.85°W., 28 lks.
A W.Fir, 30" dia., bears S.70°E., 37 lks.
A fir, 36" dia., bears N.60°E., 58 lks.
A fir, 12" dia., bears N.30°W., 26 lks.

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4660-1)

Intersect 2.25 chs. W of cor of secs. 1, 2, 11, & 12. As this intersection indicates that the N. and S. bdys of sec. 12 are not within required limits & being satisfied of the correctness of my survey and having retraced the E. bdy of sec. 12 for the purpose of fixing the point at which to restore the cor. of secs 7, 12, 13, & 18, and finding no material error thereon. I therefore begin at the cor. of secs. 1, 2, 11, & 12, which is a post firmly set witnessed and marked as described the Surveyor General, and run thence N.0°34'W. on blank line bet, secs, 1 and 2. 79.87 (chs) intersect N bdy of the Tp 1.39 chs. E of co. to secs. 1, 2, 35, & 36. As this clearly demonstrates that the error is in the measurement of the line bet. secs. 1 & 12. I therefore at point of intersection.
Set a fir post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 11 & 12 mkd C C T26S R8W on S, S12 on E & S11 on W. faces; with 1 groove on E & 5 grooves on S faces, from which -
A fir, 20" dia., bears S.74°E., 43 lks., mkd CC T26S R8W S12 BT.
A hemlock, 8" dia., bears S.63°W., 29 lks., marked CC T26S R8W S11 BT.
I erase markings for secs. 11 & 12 on old post and trees.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July/Aug. 1968- C.S. File 54/72-4

Found - Orig.8" now 14" Hemlock, alive, S.63°W. 19.1 ft., scribe visible on partially opened blaze. We open for ring count & find 70+ years overgrowth.
Orig.20" now 26" Fir, alive, S.74°E. 28.4 ft., bark scribed, partially covered w/pitch from injury above
Unrecorded 52" Fir N.45°W. 18.0 ft., shows frag. bark scribe on old blaze.
continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Closing corner Secs 11 & 12 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - Brass Cap at Cor. mkd: County Surveyors T26S R8W
Office, 1968 CC S 11|S 12
New BTs- 15" Hemlock S.46°E. 30.0 ft mkd T26S R8W S11 CC CSBT
11" Hemlock S.4°W. 36.3 ft mkd T26S R8W S12 CC CS BT
This corner lies 150 ft. west of Sec. Cor. Secs. 1 & 2 (Rec. 148.5).

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15218-9)

The orig. closing cor. of secs. 11 & 12, on the S bdy. of secs. 2, perpetuated & recorded by Tracy, in 1968, monumented with an iron post, 1½" dia., firmly set, protruding 12" above ground, with brass cap (properly) mkd.
from which the remains of the original BTs
A fir snag, 26" dia., bears S.74°E., 43 lks. with scribe marks T26S R12 BT visible on weathered bark blaze.
A sawed hemlock stump, 15" dia., bears S.63°W., 29 lks. with scribe marks T26S R8W S11 visible on opened blaze.
and bearing trees mkd. by Tracy
A hemlock, 13" dia., bears S.46°E., 46 lks. with scribe marks T26S R8W S12 CC CS BT visible on open blaze.
A sawed hemlock stump, 11" dia. bears S.4°W., 56 lks with scribe marks T26S R8W S11 CC CSBT visible on open blaze
and a new bearing tree
A hemlock, 9" dia., bears S.36½°W., 86 lks., mkd. T26S R8W S11 CC BT.
From this point the cor. of secs. 1 & 2 only, bears N.89°23'E., 2.26 chs.

Fd. & used on BLM Dependent resurvey by James E. Jelley & Wayne L Rogers, Cadastral Surveyor under Group #1128 surveyed Jan. 1983- (DCSO records Vol. 43 Page(s) 16755)

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 3/31/2026 - C.S. File 67/62-36

Found - 2½" DCSO brass cap, projecting 6" (properly mkd)
18"x5' fir snag S.76°E. 29.8 ft (rec S.74°E. 43 lks)
28" hemlock S.36½°W., 57.0 ft. (rec. 86 lks)
Corner of sec. 1 & 2 only, bears N.89°23'E., 149.2 (BLM record)
New - 8" Fir S.82°W., 27.0 ft. scribed "X" "BT" on double blaze. 3½" mag nail right side center.
8" Fir S.42°W., 12.2 ft. scribed "X" "BT" on double blaze. 3½" mag nail right side center.
continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Closing corner Secs 11 & 12 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Compass decl. $14\frac{1}{4}^{\circ}$ E.
Mon. is on bench above cut bank 45 ft. east of
logging road.

Map GIS Location:
N 43.33090° W 123.60462°