

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4652)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which

A fir, 16" dia., bears S.83°E., 770 lks., mkd: ¼ S BT.

A fir, 14" dia., bears N.58°E., 400 lks., mkd: ¼ S BT.

The trees being out of required limits, dug pits 18x18x12" in each sec. 6 ft. & raised a mound of earth, 3 ft. base, 1½ ft. high W of post. This cor. is 500 ft. below sec. cor.

Bruce Shaner, Shaner Engineering - For: Hub Lumber & Weyerhaeuser Co. - Dec. 21, 1973 - M 49-49

Found - 38" D.Fir orig. BT, scribes vis. bears S.83°E., 508.2 ft.

40" D.Fir orig. BT, scribes vis. bears N.58°E., 320.4 ft. (Rec. 264.0 ft.)

Set - Brass cap mkd: T26S R8W ¼ S25, S36 1973

New BTs- 20" D.Fir scribed "S25 ¼ BT" bears N.37°W., 15.5 ft.

12" D.Fir scribed "S36 ¼ BT" bears S.86°E., 11.0 ft.