

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4654)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
A fir, 30" dia., bears N.2°E., 205 lks., mkd: ¼ S BT.
A fir, 48" dia., bears N.72°W., 680 lks., mkd: ¼ S BT.
(out of limits)
Dug pit 18x18x12" 4 ft. N of cor.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15209)

Point for the ¼ sec. cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:
¼ S 24
 S 25
 T26S R8W
 1971

from which
A fir, 25" dia., bears N.26°E., 63 lks., mkd: ¼ S24 BT.
A fir, 5" dia., bears S.68°W., 18 lks., mkd: ¼ X BT.

Tony Hostetter, surveyed for Weyerhaeuser Co. Nov. 1998 - M131-5.

Found - 1971 BLM brass cap as described in Vol. 37 Pg. 15209
32" Fir, face evident, bears N.26°E., 41.3 ft.
9" Fir, Weyco tag & "W" nail, bears N.46°E., 4.6 ft.
16" Fir, possible face, bears S.68°W., 11.9 ft
New - 10" Fir, scribed "S24 ¼ BT" bears N.77°E., 21.0 ft.
Note - Measured dist. to new accessory is to 6" spike in root collar (below face)