

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4660)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which

A fir, 18" dia., bears N.62°W., 16 lks., mkd: ¼ S BT.

A fir, 20" dia., bears N.68°E., 10 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones - & W. Penley - Aug. 1968 - C.S. File 54/72-19

Found - Orig. 18", now 33" Fir, alive, N.62°W. 10.6 ft., find "¼" bark scribe in poor condition.

Orig. 20", now 42" Fir, alive, S.68°W., (rec. N.68°E.) 6.6 ft. shows "B" bark scribe in poor condition, upper axe blaze chopped off previously

Set - Brass Cap at cor. mkd: County Surveyors T26S R8W
Office ¼ S 12
S 13

New BTs- 30" D.Fir N.4°W., 6.8 ft. Mkd: "¼ S12 CS BT"

42" D.Fir S.68°W. 6.6 ft (orig BT) Mkd "¼ S13 CS BT"

This corner lies on top of ridge, course E & W.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 739, surveyed May/July 1971 - (DCSO Records Vol. 37 Page(s) 15215-6)

The ¼ sec. cor. of secs. 12 & 13, perpetuated & recorded by Tracy, in 1968, monumented with an iron post, 1½" dia. firmly set, protruding 8" above ground, with brass cap mkd.

T 26 S
¼ S 12
S 13
R 8 W
1968

from which the original bearing trees

A fir, 42" dia., bears S.68°W., 11 lks., with scribe mark B visible on bark blaze & re-marked by Tracy, in 1968, with scribe marks ¼ S13 CS BT visible on open blaze. (Record, N.68°E.)

A fir, 33" dia., bears N.62°W., 16 lks., with scribe mark ¼ visible on weathered bark blaze.

and a bearing tree mkd. by Tracy, in 1968

A fir, 30" dia., bears N.4°W., 11 lks., with pitched over blaze.

continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Geisler, LS 1988 - For: Champion International
Sept/Dec 1983 - M90-49

Found - 1968 Doug. Co. Brass cap on 1½" iron pipe.
36" fir bears N.4°W., 6.8 ft. Scribe marks visible
on chopped face. (1968)
42" fir, down & uprooted, Scribe marks visible on
chopped face. Root hole bears S.68°W., 7.3 ft.
(Rec. N.68°E.) 1968
New BT - 6" fir bears S.79°W., 39.6 ft. scribed, ¼ S13 BT

BLM resurvey by Timothy Moore, Cadastral Surveyor & Robert
Browning, Survey Technician, under Group #1990, surveyed July
2001/Sept. 2002 - (DCSO records Vol. 54 Page(s) 21039)

The ¼ sec. cor. of secs. 12 & 13, monumented with an iron
pipe, 1¼" dia., firmly set, 3" below the surface of the
ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A roothole, with a fir trunk, 42" dia., lying alongside,
bears S.68°W., 7.3 ft., trunk has scribe marks S13 CS
BT visible on opened blaze.
and the remains of a BT mkd. by Powell, in 1968 (Peterson &
Berry report this tree as being mkd. by Tracy.)
A sawed fir stump, 34" dia., bears N.4°W., 7.3 ft., with
a healed blaze.
and a bearing tree mkd. by Geisler, in 1983
A fir, 12" dia., bears S.79¼°W., 39.7 ft., with a healed
double blaze.
and a new bearing tree
A fir, 6" dia., bears N.27°E., 19.2 ft., mkd. X BT.
Corner is located on top of a ridge, bears East and West.