

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 36, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A. R. and S.C. Flint, Under Contract #392,
dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3930)

Set Cedar ¼ post 3 ft. long, 3" sq., from which
A Cedar 30" dia., bears N.50°E., 23 lks. dist.
A Fir 30" dia., bears S.35°E., 40 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept. 26, 1968 - C.S. File 54/72-33

Found - Orig. 30" Fir, now 48" stump, S.35°E., 26.4 ft.,
only small trace of bark scribe remains.
Cruiser's marks and yellow tag on SE. BT,
recorded in forest appraisal survey, dated Nov.
1951 by Lecklider & Givens.

No trace of NE. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T25S R8W S 36
T26S S 1

1968

New BTs- 14" Hemlock S.68°W., 50.4 ft. mkd. ¼ S1 CS BT.

10" Cedar N.87°E., 28.4 ft. mkd. ¼ S36 CS BT.

Corner lies on very steep N. slope about 100 ft. S. of creek,
course E. We put yellow line tag at creek about 100 ft. N.
of corner.

BLM resurvey by Peter Peterson and Daniel Berry, Cadastral
Surveyors under Group #739, surveyed May/July 1971 (DCSO
records Vol. 37 Page(s) 15207-08)

The ¼ sec. cor., perpetuated and recorded by the County in
1971, monumented with an iron post 2" dia., firmly set,
protruding 10" above ground, with brass cap mkd. in 1971,
from which the original bearing tree

A Fir stump 30" dia., bears S.35°E., 40 lks. dist. with
fragmentary scribe marks visible on weathered bark
blaze.

and bearing trees by the County

A Cedar 11" dia., bears N.87°E., 43 lks. dist., mkd. ¼ S36
CS BT.

A Hemlock 15" dia., bears S.67°W., 76 lks. dist. mkd. ¼ S1
CS BT.