

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. sec. 13; & 18 of T. 26-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4590)

Set ¼ sec. post, from which
 A Fir 30" dia., bears N.80°W., 16 lks. dist.
 A Fir 10" dia., bears S.80°E., 25 lks. dist.

GLO survey by S.C. Flint, under contract #392 dated May 1881 (DCSO records, Volume 11 Page 4619)

Quarter post gone. Witness trees all found. Made and set firmly in the ground, a Hemlock post 3 ft. long, 3" Square, from which, the witness trees bear as follows:
 A Fir 10" dia., bears N.80°W., 16 lks. dist.
 A Fir 10" dia., bears S.80°E., 25 lks. dist.

Bureau of Land Management survey by Peterson and Berry, under Group #739. Survey May/July 1971 (DCSO records, Volume 37 Page 15199)

Point for the ¼ sec. cor., determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Set an Iron post, 28" long, 2½" dia., 8" in the ground, to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd:

 1/4
 S 13 | S 18
 T 26 S
 R 8 W R 7 W
 1971

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.

There are no suitable bearing trees within limits.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21040-1)

The ¼ sec. cor. of secs. 13 & 18 on the E. bdy. of the Tp., monumented with an iron post, 2½", firmly set, flush with a mound of stone, 3½ ft base, to top, w/brass cap (properly) mkd
A mound of stone, 4 ft. base, 2½ ft. high, is located SW. of corner. (Record, West.)

from which new bearing trees

 A fir, 4", bears S. 32° E., 9.3 ft., mkd. X BT.

 A fir, 10", bears N. 20° W., 9.1 ft., mkd. ¼ S13 BT.

continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13; 18, T26-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Corner is located on a very steep N. slope and South, 70 ft., (and 70 ft. in elevation) above a ravine, course S.70°E. Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Pg 22468)

The ¼ sec. cor. of secs. 13 and 18, monumented with an iron post, 2½" dia., firmly set, flush with a mound of stone, 3½ ft. base to top, with brass cap mkd.

¼
S 13|S 18
T 26 S
R 8 W R 7 W
1971

from which bearing trees mkd. by Moore and Browning in 2002
A fir, 5" dia., bears S.32°E., 9.3 ft., with partially healed blaze.
A fir, 11" dia., bears N.20°W., 9.1 ft., with partially healed blaze.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 7/2019 - C.S.
File 65/102-70

Found - BLM brass cap (properly mkd)
6" Fir S.32°E., 9.3 ft. good scar.
12" Fir N.20°W., 9' ft. good scar.
New - 3" Fir S.70°W., 4.2 ft. scribed X
9" Fir S.21°W., 9.2 ft. scribed ¼ S13 BT.
6' alum post 5 ft south.
Note - Compass decl. 15½°E.