

PRIMARY CORNER DESCRIPTION WC Sec. Cor. 12 & 13; 7 & 18 of T. 26-7

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Pages 4589-90)

 Marked a Fir, 15" dia., for cor secs 7, 18, 12 & 3, from which
 A Fir 12" dia., bears N.10°W., 32 lks dist.
 A Fir 8" dia., bears N.15°E., 21 lks. dist.
 A Fir 24" dia., bears S.8°W., 160 lks. dist.
 A Laurel 10" dia., bears S.50°E., 20 lks. dist.

GLO survey by S.C. Flint, Contract #392, 1881, found Corner tree & all witness trees. (DCSO record, Vol. 11 Pgs. 4618-19)

Bureau of Land Management survey by Peterson & Berry, under Group #739. Survey May/July 1971 (DCSO recs, Vol 37 Pg 15200)

 True point for the cor. of secs. 7, 12, 13 and 18, falls on rock outcropping, 40 ft. high, slopes E.; determined by the method of irregular boundaries; there is not remaining evidence of the original corner.
 (.50 chs. N.0°07'W., point selected for the witness corner of secs. 7, 12, 13 and 18)
 Seat a brass tablet, 3" dia., 3½" stem, in a drill hole in solid rock, mkd.

T 26 S
R 8 W R 7 W
S 12 S 7
S 13 S 18
↓
W C
1971

from which
 A Madrone 5" dia., bears N.84½°E., 68 lks mkd. X BT.
 A Madrone, 4" dia., bears S.61½°W., 90 lks. mkd. X BT.
 A Fir 20" dia., bears N.44°W., 125 lks. mkd. X BT.
 No other trees available within limits.
 The witness corner is located at top of ascent, slopes S.60°E.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21037-8)

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22077)

 The WC for the cor. of secs. 7, 12, 13, & 8, monumented with a brass tablet, 3" dia., cemented firmly into solid bedrock, (properly) mkd. continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 700501

PRIMARY CORNER DESCRIPTION WC Sec. Cor. 12 & 13; 7 & 18 of T. 26-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which bearing trees mkd. by Peterson and Berry

A madrone, 11" dia., bears N.73½°E., 36.4 ft., with a healed double blaze.

A madrone, 8" dia., bears S.59°W., 41.5 ft., with fragmentary scribe marks visible on partially healed blaze.

A fir, 28" dia., bears N.45¼°W., 63.8 ft., with a healed blaze.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 7/2019 - C.S.
File 65/102-71

Found - BLM brass cap (properly mkd)
11" madrone N.73½°E., 36.4 ft. good scar.
9" madrone S.59°W., 41.5 ft. good scar.
30" fir N.45¼°W., 63.8 ft. good scar.
New - 4" W.Fir N.43°E., 17.8 ft. scribed WC BT
Note - Compass decl. 15½°E.