

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12; & 7 of T.26-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4589)

Set ¼ sec. post from which
 A Laurel 12" dia., bears N.42°W., 15 lks. dist.
 A Fir 30" dia., bears S.10°E., 27 lks. dist.

GLO survey by S.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Volume 11 Page 4618)

Quarter post gone. Old witness trees found. Made new Laurel post 3 ft. long 3" sq. and set firmly in the ground from which
 Laurel 12" dia., bears N.42°W., 15 lks. dist.
 Fir 30" dia., bears S.10°E., 27 lks. dist.

BLM resurvey by Peterson and Berry under Group #739. Survey May/July 1971 (DCSO records, Volume 37 Page 15201)

Point for the ¼ sec. cor., determined by the method of irregular boundaries; there is no remaining evidence of the original corner.
Set an ironpost, 28" long 2½" dia., 15" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:
 1/4
 S 12 | S 7
 T 26 S
 R 8 W R 7 W
 1971

from which
 A Fir 10" dia., bears East, 60 lks dist., mkd. ¼ S7 BT.
 A Fir 33" dia., bears S.32°W., 51 lks. mkd. ¼ S12 BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22078)

The ¼ sec. cor. of secs. 7 & 12, on the W. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 7" above a mound of stone 3 ft. base to top, with brass cap (properly) mkd.
from which bearing trees mkd. by Peterson and Berry
 A fir, 19" dia., bears S.85¾° E., 37.4 ft., with a healed blaze. (Record, East, 39.6 ft.)
 A fir, 49" dia., bears S.32°W., 33.7 ft., with a healed blaze.