

PRIMARY CORNER DESCRIPTION Cor. Secs. 33 & 34 only (South)

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4729)

Set hemlock post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 3, 4, 33 & 34, marked T26S S34 on NE, R9W S3 on SE, T27S S4 on SW & S33 on NW faces, with 3 notches on E & W edges; from which

A fir, 60" dia., bears N.42°E., 24 lks, T26S R9W S34 BT.

A fir, 56" dia., bears S.57°30'E., 52 lks., T27S R9W S3 BT

A fir, 56" dia., bears S.8°W., 27 lks., T27S R9W S4 BT.

A fir, 60" dia., bears N.70°45'W. 81 lks., T26S R9W S33 BT

This cor. is 500 ft. above the ¼ sec. cor.

BLM dependent resurvey by Owen Chatters II & Jack W. Bowder, Cadastral Surveyors, under Group #'s 350 & 791, surveyed 1972/1977 - (DCSO records C.S. File 65/52-19 A-C)

The Cor. of secs. 33 & 34 only, on the S bdy of the Tp., monumented with an iron pipe, 12" long, ¾" dia., firmly set, projecting 4" above ground, from which the remains of the orig. BTs:

A sawed fir stump, 70" dia., bears N.42°E., 21 lks., with scribe marks BT visible on bark. (Rec. 24 lks.)

A sawed fir stump, 72" dia., bears S.12°E., 50 lks., with scribe marks T27S R9W S3 BT visible on bark. (Rec. S.57½°E., 52 lks.)

A sawed fir stump, 65" dia., bears S.22°W., 29 lks., with scribe marks T27S R9W S4 BT visible on bark. (Rec. S.8°W., 27 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, with brass cap mkd.

T 26 S R 9 W

S 33 | S 34

S 4

T 27 S

1973

from which new bearing trees

A fir, 12" diam., bears N.30°E., 33½ lks., mkd. T26S R9W S34 BT.

A fir, 10" diam., bears N.60°W., 26 lks., mkd. T26S R9W S33 BT.

continued next page

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33 & 34 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Edith M. Forkner, Cadastral Surveyor under Group #2005, surveyed 2002/2003 (DCSO rec. Vol. 54 pg(s) 20990)

The cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap mkd.

T26S R9W
S 33|S 34
S 4
T27S
1978

from which the remains of the original bearing trees

A sawed fir stump, 68" dia., bears N.42°E., 12.2 ft., no marks visible. (Record, 13.9 ft.)

A sawed fir stump, 68" dia., bears S.57½°E., 33.0 ft., with scribe marks R9W BT visible on bark blaze. (Record, S.12°E.)

A sawed fir stump, 62" dia., bears S.22°W., 17.1 ft., with scribe marks T27S R9W visible on bark blaze. (Record, 19.1 ft.)

and the bearing trees mkd. by Chatters and Bowder

A fir, 17" dia., bears N.10¾°E., 22.1 ft., with a healed blaze. (Record, N.30°E.)

A fir, 21" dia., bears N.56°W., 17.2 ft., with a healed blaze. (Record, N.60°W.)