

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

ON THE COOS COUNTY LINE - SEE COOS COUNTY SURVEYORS OFFICE FOR POSSIBLE ADDITIONAL RENEWAL REPORTS

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4755)

Set hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd: ¼ S on W face, from which
A fir, 38" dia., bears N.33°W., 69 lks., mkd: ¼ S BT.
A fir, 34" dia., bears N.34°E., 39 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #350, surveyed June/July 1973 - (DCSO records Vol. 39 Page(s) 15959)

The ¼ sec. cor. of secs. 33 & 34, determined at record dist from the remains of the original bearing trees:
A fir snag, 54" dia., bears N.34°E., 39 lks., with illegible scribe marks visible on opened blaze.
A fir stump, 48" dia., bears N.37°W., 69 lks., no marks visible. (Record, N.33°W.)
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.
T26S R9W
¼
S 33|S 34
1973
from which new BTs
A fir, 7" dia., bears S.24°E., 85 lks., mkd: ¼ S34 BT.
A fir, 10" dia., bears S.39°W., 87½ lks., mkd: ¼ S33 BT.