

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 28" dia., bears N.9°E., 64 lks., with healed blaze.
A fir, 20" dia., bears S.7°E., 52 lks., with healed blaze.
A fir, 20" dia., bears S.76°W., 17 lks., with healed blaze
A fir, 20" dia., bears N.41°W., 13 lks., with scribe marks
SE S9 BT visible on opened blaze.

Robert C. Adamek, Weyerhaeuser Co. Dellwood Engineering
Office Williams River No. 2 survey - March 27, 1975 - M55-60
& C.S. File 58/42

Found - BLM monument from which
16" D.Fir, bears S.40°W., 57 lks.
10" Hemlock bears S.47°E., 31 lks.
10" Maple, bears N.13°E., 38 lks.
12" D.Fir bears N.28°W., 45 lks.
There is also a 2" alum. pipe set by Menasha Corp. It is
improperly located according to BLM sources & GLO notes.

Tony Hostetter - For: Roseburg Resources - 1/20/2023 - C.S.
file 65/111-44

Found - 1973 BLM brass cap as set by Rogers, Vol 39, Pg
15961-62.
20" Fir snag, BLM BT, face evident, bears; S.40°W.,
37.6 ft to center.
20" Hemlock snag, BLM BT, face evident, bears;
S.47°E., 20.5 ft to center.
24" Fir snag, BLM BT, face evident, bears; N.28°W.,
29.7 ft to center.
2" Aluminum pipe, Ellingsen 1962, bears, S.46°57'W.,
7.58 ft.
New BTs- 10" Fir, marked "X", BT tag, bears; N.21°17'E., 15.1
ft to spike, placed in root collar below tag.
16" Fir, marked "X", BT tag, bears; S.21°41'E., 10.3
ft to spike, placed in root collar below tag.
11" Fir, marked "X", BT tag, bears; S.26°35'W., 12.5
ft to spike, placed in root collar below tag.
10" Fir, marked "X", BT tag, bears; N.52°32'E., 5.3
ft to spike, placed in root collar below tag.