

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4729)

Set Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which

A Fir 10" dia., bears N.22°45'E., 20 lks. dist. mkd. ¼ S BT.

A Hemlock 14" dia., bears S.29°E., 15 lks. dist. mkd. ¼ S BT.

Tony Hostetter - For: Weyerhaeuser & Menasha - March 1996 - M 126-61

Found - 3/4" I.P., 1 ft. out of ground, from which
10" decayed stump, bears S.26°E., 10.4 ft. (14" Hemlock S.29°E., 15 lks., 9.9 ft. GLO rec.)
13" Hemlock, WEYCO tag, bears N.28°W., 19.6 ft.
18" Hemlock, cruisers marks, bears S.88°E., 20.4 ft.
43" Fir, WEYCO tag, cruiser marks, bears S.36°W., 25.1 ft.