

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4756)

Set hemlock post 3 ft. 3" sq., 24" in the ground for ¼ sec. cor. mkd: ¼ S on N face, from which:
A fir, 33" dia., bears N.1°E., 6 lks., mkd: ¼ S BT.
A fir, 38" dia., bears S.66°30'E., 25 lks., mkd: ¼ S BT.

Weyerhaeuser reports received June 17, 1970 C.S. File 55/155B

Date: June 10, 1954
38" Fir S.66½°E., 25 lks.
33" Fir N.1°E., 6 lks.
Witnessed by Howard T. Henderson

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - John Powell - Gary Langlitz (guest witness) - 5/26/1982 - C.S. File 61/36-18

Found - Unrecorded 3/4" I.P. protruding 9" out of ground. from which:
Orig. 38" now 52" fir stump with good double scars bears S.66½°E., 16.5 ft.
Orig. 33" fir taken out by cat road.
Set - At the location of the found ¾" I.P. I SET a 1"x30" I.P. with brass cap attached marked "Douglas Co Surveyor T26S S27 S34 ¼ R9W 1982.
I place found IP along southerly edge of brass cap.
New - Spike in top of 48" fir stump bears N.60°W., 21.7 ft
8" hemlock scribed "¼ S27 CS BT" in double blaze bears N.4°W., 49.5 ft.
Spike in top of 36" fir stump bears N.1°W., 46.6 ft.

Fd. Ok by T. Hostetter, 3/1996 - M126-61