

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

**ON THE COOS COUNTY LINE - SEE COOS COUNTY
SURVEYORS OFFICE FOR POSSIBLE ADDITIONAL
RENEWAL REPORTS**

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4758)

Set a sand stone 15x12x10" 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A cedar, 13" dia., bears S.60°E., 36 lks., mkd: ¼ S BT.
A cedar, 26" dia., bears N.47°W., 88 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - John Powell - 6/2/1982 - C.S. File 61/36-19

Found - Orig. 15x12x10" sandstone, now 15x10x7" with "¼ S" visible on north face. Stone was firmly set protruding 5" out of ground.
Orig. 13" now 24" cedar, previously opened showing rotted face with no scribing visible, bears S.64°E., 23.8 ft. (Rec. S.60°E.)
Orig. 26" now 32" cedar previously opened showing rotted face with no scribing visible, bears N.51°W., 58.1 ft. (rec. N.47°W.)
Set - At the location of the found stone I SET a 1"x30" IP with brass cap attached marked "Douglas Co Surveyor T26S ¼ S22 S27 R9W 1982", protruding 8" out of the ground.
I place orig. stone along north edge of brass cap and leave it protruding 5" out of ground.
New BTs- 11" hemlock scribed "¼ S22 CS BT" in double blaze bears N.46°E., 36.9 ft.
I rescribe orig. 13" now 24" cedar "¼ S27 CS BT" in double blaze
I rescribe orig. 26" now 32" cedar "¼ S22 CS BT" in double blaze.
Sketch in C.S. file.