

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4762)

Set laurel post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N face, from which
A laurel, 4" dia., bears S.1°30'E., 10 lks., mkd: ¼ S BT.
A laurel, 4" dia., bears N.40°W., 21 lks., mkd: ¼ S BT.

Robert C. Adamek, Weyerhaeuser Co. Dellwood Engineering Office Williams River No. 2 survey - March 27, 1975 - M55-60 & C.S. File 58/42

No evidence of orig. corner or its accessories was found. The cor. was re-established by the single proportion method.
Set - 1" IP from which
12" Madrone bears N.81°W., 32.0 ft. scribed ¼ S10 RP
24" D.Fir bears S.82°E., 29.1 ft. scribed ¼ S15 RP

1