

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4764)

-----

Set fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N face from which

    A cedar, 22" dia., bears N.32°W., 67 lks., mkd: ¼ S BT.

    A fir, 22" dia., bears S.6°E., 34 lks., mkd: ¼ S BT.

Robert C. Adamek, Weyerhaeuser Co. Dellwood Engineering Office Williams River No. 2 survey - March 27, 1975 - M55-60 & C.S. File 58/42

-----

Position of this corner is occupied by a small hemlock stub. Orig. BTs were destroyed by road construction. Re-referenced by Weyerhaeuser Co. Engineers.

    22" Hemlock bears N.01°W., 17.9 ft.

    28" D.Fir bears S.69½°E., 30.0 ft.