

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 and 34, T25-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John W. Meldrum, U.S. Deputy Surveyor, under contract #663, dated May 21, 1896 - (DCSO records Vol. 10 Page(s) 4020)

-----

Set Fir post 3 ft. long, 4" sq. 24" in the ground for ¼ Sec. cor. mkd: ¼ S. on N face, from which

A Laurel, 4" dia., bears N.26°W., 22 lks., mkd: ¼ S BT.

A Fir, 40" dia., bears S.24°W., 85 lks., mkd: ¼ S BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 55/155B-2 - Filed 6/17/1970

-----

40" D.Fir "W" nail & tag N.27°E., 51.3 ft.

18" D.Fir "W" nail & tag S.85½°W., 17.3 ft.

This information added to the corner report on 9/26/2001.  
DCSO