

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, Deputy Surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4730)

Set Hemlock post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 2, 3, 34 and 35, mkd. T26S S35 on NE.; R9W S2 on SE.; T27S S3 on SW.; and S34 on NW. faces, with 2 notches on E. and 4 notches on W. edges, from which
A Fir 22" dia., bears N.75°E., 30 lks. dist., mkd. T26S R9W S35 BT.
A Fir 12" dia., bears S.16°E., 18 lks. dist. mkd. T27S R9W S2 BT.
A Fir 24" dia., bears S.70°30'W., 34 lks. dist. mkd. T27S R9W S3 BT.
A Fir 24" dia., bears N.8°W., 31 lks. dist. mkd. T26S R9W S34 BT.

Tony Hostetter - For: Weyerhaeuser & Menasha - March 1996
M 126-61

Found - 40" Fir stump, possible face, burned corner tag, (GLO rec. N.8°W., 31 lks. (20.5 ft.)) bears N.3°W., 20.5 ft.
42" Fir stump, face evident, 2 nail & a melted corner tag, (GLO rec. S.70½°W., 34 lks., 22.4 ft.) bears S.68°W., 22.4 ft.
Set 5/8" x 36" rebar with plastic cap mkd. "HOSTETTER LS 1975", from which
45" Fir stump, WEYCO tag and 6" spike, bears S.25°E., 49.8 ft.