

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4744-5)

Set vine maple post, 3 ft. long, 3" sq., 24" in the ground for cor. of secs. 26, 27, 34, & 35, mkd T26S S26 on NE, R9W S35 on SE, S34 on SW, & S 27 on NW faces, with 1 notch on S & 2 notches on E edges, from which
A fir, 45" dia., bears N.29°E., 190 lks., mkd: T26S R9W S26 BT.
A fir, 32" dia., bears S.38°30'E., 182 lks., mkd: T26S R9W S35 BT.
A fir, 50" dia., bears S.8°30'W., 38 lks., mkd: T26S R9W S34 BT.
A fir, 30" dia., bears N.87°15'W., 68 lks., mkd: T26S R9W S27 BT.

Tony Hostetter - For: Weyerhaeuser Co. & Menasha Corp. - March 1996 -M 126-61

Set - 5/8"x36" rebar w/plastic cap mkd: "HOSTETTER LS 1975"
40" Fir snag, no marks, possible face, bears N.27°45'E., 128.4', (GLO rec. Fir, N.29°E., 190 lks., 125.4') OBT.
39" Fir snag, visible axe marks, face evident, bears S.39°E., 119.6', (GLO rec. S.38½°E., 182 lks., 120.0') OBT
48" Fir snag, visible axe marks, face evident, bears S.9°W., 25.1' (GLO rec. S.8°30'W. 38 lks. 25.1') OBT
40" Fir snag, visible axe marks, face evident, bears N.84°15'W. 44.9', (GLO rec. N.87°15'W., 68 lks. 44.9') OBT
18" Fir, bears N.27°15'E., 99.2', scribed "S 26 T26S R9W BT"
24" Fir, bears S.41°E. 79.8' scribed "S 35 T26S R9W BT"
16" Fir, bears S.39°30'W., 19.8', scribed "S 34 T26S R9W BT"
25" Fir, bears N.14°30'W., 58.2', scribed "S 27 T26S R9W BT"