

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor Secs 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4748)

Set maple post 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 14, 15, 22, & 23, marked T26S, S14 on NE, R9W, S23 on SE, S22 on SW & S15 on NW faces, with 3 notches on S & E edges from which

- A fir, 12" dia. bears N.40°E. 42 lks. mkd: T26S R9W S14 BT
- A fir, 7" dia. bears S.68°E., 39 lks. mkd: T26S R9W S23 BT
- A fir, 14" dia., bears S.10°30'W., 41 lks., mkd: T26S R9W S22 BT.
- A fir, 12" dia., bears N.66°15'W., 42 lks., mkd: T26S R9W S15 BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #350, surveyed June/July 1973 - (DCSO records Vol. 39 Page(s) 15957-8)

The cor. of secs. 14, 15, 22, & 23, determined at record distance from the remaining original BTs

- A fir, 22" dia., bears N.10½°E., 42 lks., with illegible scribe marks visible on opened blaze. (Record, N.40°E.)
- A fir, 36" dia., bears S.68°E., 39 lks., with illegible scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T26S	R9W
S 15	S 14
S 22	S 23
1973	

from which new bearing trees

- A fir, 20" dia., bears S.29°W., 70½ lks., mkd. T26S R9W S22 BT.
- A fir, 22" dia. bears N.21°W. 67 lks. mkd. T26S R9W S15 BT

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2008 - M158-41

Found - 2½" IP bent, 1973 brass cap gone (Vol. 39 Pg 15957)
36" fir stump, OBT, BLM tag, bears S.68°E., 25.7 ft.

New BTs- 10" fir, scribed "S14 SW BT", bears N.45°E., 7.7 ft. to spike.
5" fir, scribed "S22 NE BT", bears S.44°W., 4.7 ft. to spike.
7" fir, scribed "S15 SE BT", bears N.31°W., 13.7 ft. to spike.