

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4750)

Set maple post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face from which
An alder, 13" dia., bears S.23°E., 127 lks., mkd: ¼ S BT.
A fir, 8" dia., bears N.65°30'W., 3 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #350, surveyed June/July 1973 - (DCSO records Vol. 39 Page(s) 15958-9)

The ¼ sec. cor. of secs. 14 & 15, determined at record bearing & distance from the remains of the orig. BTs:
A decayed alder root crown, size indeterminate, bears S.23°E., 127 lks., no marks visible.
A fir, 40" dia., bears N.65½°W., 3 lks., with scribe mark T visible on opened blaze.

At the corner point
Set an iron post. 28" long, 2½", diam., 22" in the ground, with brass cap mkd.
T26S R9W
¼
S 15|S 14
1973

from which a new bearing tree
A W.Fir, 36" dia., bears S.18°E., 142 lks., mkd: ¼ S14 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2008 - M158-41

Found - 2½" IP with 1973 BLM brass cap. (Vol. 39 Page 15958)
40" Fir stump, OBT, BLM tag, bears N.65°W., 3.6 ft.
New BTs- 11" fir, scribed "S14 ¼ BT", bears N.53°E., 14.4 ft. to spike.
11" fir, scribed "S14 ¼ BT", bears S.78°E., 9.8 ft. to spike.
10" fir, scribed "S15 ¼ BT", bears S.11°W., 1.5 ft. to spike.