

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4752)

Set laurel post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face from which

A laurel, 4" dia., bears N.15°E., 22 lks., mkd: ¼ S BT.

A laurel, 4" dia., bears N.66°30'W., 22 lks., mkd: ¼ S BT.

Robert C. Adamek, Weyerhaeuser Co. Dellwood Engineering Office Williams River No. 2 survey - March 27, 1975 - M55-60 & C.S. File 58/42

No evidence of the orig. corner or its accessories was found. The corner was reestablished by single proportional method.

Set - A 1" iron pipe from which:

24" D.Fir, bears S.43°W. 36.1 ft. scribed ¼ COR S 10 RP

14" Madrone bears S.60°E. 12.0 ft. scribed ¼ COR S11 RP