

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4749)

Set maple post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
A fir, 24" dia., bears N.48°30'E., 49 lks., mkd: ¼ S BT.
A fir, 26" dia., bears S.48°30'W., 24 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #350, surveyed June/July 1973 - (DCSO records Vol. 39 Page(s) 15958)

The ¼ sec. cor. of secs. 14 & 23, determined at rec. bearing & distance from the original bearing trees:
A fir, 40" dia., bears N.48½°E., 49 lks., with healed blaze.
A fir, 50" dia., bears S.48½°W., 24 lks., with scribe marks ¼ S BT visible on bark.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.
T26S R9W
¼ S 14
S 23
1973

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2008 - M158-41

Found - 2½" IP with 1973 BLM brass cap & both orig. BTs (now stumps) as described by Rogers in 1973 (Vol 39 Pg. 15958)
New BTs- 4" fir, spike & tag, not scribed, bears S.23°E., 2.7 ft. to spike.
8" fir, spike & tag, not scribed, bears N.2°W., 8.4 ft. to spike.