

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4739)</p> <p>-----</p> <p>Set maple post 3 ft. long, 3" sq., for ¼ sec. cor. mkd ¼ S on W face, from which</p> <p> A fir, 20" dia., bears S.21°E., 41 lks., mkd: ¼ S BT.</p> <p> A fir, 60" dia., bears S.46°40'W., 27 lks., mkd: ¼ S BT.</p>
<p>Weyerhaeuser reports received June 17, 1970 C.S. 55/155B-6</p> <p>-----</p> <p>Date: 7/63</p> <p> 72" DF "W" nail & tag, S.44½°W., 20.2 ft. OBT</p> <p> 36" DF "W" nail & tag, N.65°W., 66.2 ft.</p> <p>By Whom: Stevens, Kunkle, Smith</p>
<p>Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2008 - M158-41</p> <p>-----</p> <p>Found - ½" copper pipe & BTs as described by Weyerhaeuser in 1970 C.S. 55/155B)</p> <p> 72" Fir stump, Weyerhaeuser tag, bears S.44°W. 20.2'</p> <p>New BTs- 20" Fir stump, BT tag, bears N.68°E., 42.2 ft. to spike.</p> <p> 20" Hemlock stump, BT tag, bears S.67°W., 3.7 ft. to spike.</p>
<p> </p>