

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4741-2)

-----

Set cedar post, 3 ft. long, 3" sq., 24" in the ground for cor. of secs. 1, 2, 11, & 12 mkd: T26S, S1 on NE, R9W, S12 on SE, S11 on SW & S2 on NW faces, with 5 notches on S & 1 notch on E edges, from which

- A fir, 20" dia., bears N.21°45'E., 65 lks., mkd: T26S R9W S1 BT.
- A fir, 30" dia., bears S.78°45'E., 124 lks., mkd: T26S R9W S12 BT.
- A fir, 36" dia., bears S.50°15'W., 58 lks., mkd: T26S R9W S11 BT.
- A fir, 38" dia., bears N.33°45'W., 73 lks., mkd: T26S R9W S2 BT.

Robert C. Adamek, Dellwood Dist. Engineer - For: Weyerhaeuser - Sept. 23, 1974 - M 54-75 & C.S. 58/23

-----

The orig. cor. & its accessories were destroyed by road construction. The cor position was referenced by Weyerhaeuser Co. engineers prior to destruction.

Set - 1" I.P. from which:

- 30" D.Fir, bears N.21°E., 41.2 ft.
- 16" D.Fir, bears S.55½°E., 46.1 ft.
- 48" D.Fir, bears S.12°W., 57.6 ft.