

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Cor Secs 1 & 2; 35 & 36 T25-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #662, dated December 16, 1866 (DCSO records Vol. 10 Page(s) 4021-2)

Set myrtle post 3 ft long, 4" sq. 24" in the ground for cor. of secs. 1, 2, 35, & 36, marked: T 25 S S 36 on NE, R 9 W S 1 on SE, T 26 S S 2 on 5 notches on W edges, from which

- A Fir, 4" dia., bears N.36°45'E., 118 lks., mkd: T25S R9E S36 BT.
- A Maple, 4" dia., bears S.18°40'E., 117 lks., mkd: T26S R9E S1 BT.
- A Fir, 12" dia., bears S.58°W., 78 lks., mkd: T26S R9E S2 BT.
- A Fir, 15" dia., bears N.55°W., 99 lks., mkd: T25S R9E S35 BT.

Survey by Robert C. Adamek - For; Weyerhaeuser Co. - Feb. 2, 1977 (added 3/29/2023) - C.S. File 58/135; M 63-19

Found one original BT with visible scribe marks:
36½" D.Fir bears N.58°E., 78 lks.
Note: OBT is SW (JC 3/29/2023)

Tony Hostetter - For: Weyerhaeuser Co. - March 2023 - M182-21

Found - GLO BT 40" Cedar at S.58°W., described below, bearing listed by Adamek as N.58°E.
Calculated position based on record bearing and distance from 16th corner to the south as shown (M63-19). From which: All measurements listed are from the calculated position.

- 5/8" Iron rod with plastic cap marked "HOSTETTER LS 1975" as witness corner bears; S.89°45'53"W., 47.25 ft from calculated corner position.
- 44" Cedar, WEYCO TAG, no other marks, bears; S.40°05'W., 41.5 ft to spike (new).
- 40" Fir, BLM tag, no other marks bears; S.57°42'W., 51.7 ft to spike (new).
- Original GLO BT (rec. S.58°W., 78 lks, 51.5 ft)

New BTs- (MEASUREMENTS FROM CALCULATED POSITION.)

- 12" Fir, marked "X", BT tag, bears; N.83°37'E., 21.3 ft to spike below "X".
- 10" Alder, marked "X", BT tag, bears, N.41°33'E., 4.96 ft to spike below "X".