

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 639500

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy Surveyor, under contract No. 662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4740-1)

Set Vine maple post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S, on N face from which
A maple, 12" dia., bears N.58°E., 52 lks., mkd: ¼ S BT.
A maple, 15" dia., bears S.40°W., 3 lks., mkd: ¼ S BT.

Weyerhaeuser reports received June 17, 1970 C.S. 55/155B-5

Date: 7/63
Pipe
20" Myrtle "W" nail-tag N.79¾W., 40.4 ft.
By Whom: Stevens, Kunkle, Smith

Robert C. Adamek, Dellwood Dist. Engineer - For: Weyerhaeuser - Sept. 23, 1974 - M 54-75 & C.S. 58/23

No trace of the original corner or its accessories were found. Restored this cor. by the single proportion method but was unable to mark the true position permanently because of a large pile of debris.
Set - 1" I.P. N.85°39.7'W., 54.46 ft. of true position for witness cor. Witness cor. referenced as follows:
18" stump bears N.25°36.2'E., 14.5 ft.
30" stump bears S.21°00.2'W., 70.9 ft.

1