

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T26-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4647)

-
- Set Cedar post 4 ft. long, 4" sq., from which
- A Fir 40" dia., bears N.45°E., 36 lks. dist.
 - A Fir 36" dia., bears N.30°W., 75 lks. dist.
 - A Fir 36" dia., bears S.35°W., 28 lks. dist.
 - A Fir 40" dia., bears S.53°E., 72 lks. dist.

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4721)

Set Laurel post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 19, 24, 25 and 30, marked T26S S19 on NE.; R8W S30 on SE.; S25 on SW.; and R9W S24 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which

- A Fir 40" dia., bears N.30°30'E., 47 lks. dist. mkd. T26S R8W S19 BT.
- A Fir 40" dia., bears S.62°E., 155 lks. dist. mkd. T26S R8W S19 BT.
- A Fir 50" dia., bears S.40°30'W., 93 lks. dist. mkd. T26S R9W S25 BT.
- A Fir 36" dia., bears N.43°15'W., 50 lks. dist. mkd. T26S R9W S24 BT.

From this cor., the old cor. which is a Cedar post witnessed as described by the surveyor general, bears S.3°23'W., 10.02 chs. dist. I destroy the post, which is still standing but much decayed and obliterate the marks from the old BTs.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14176-77)

-
- The Sec. Cor., determined from the original bearing trees:
- A burned Fir stump 34" dia., bears N.30½°E., 47 lks. dist., with no marks remaining.
 - A Fir 65" dia., bears S.52°E., 160 lks. dist., with fragmentary scribe marks visible on weathered bark blaze. (Rec. S.62°E., 155 lks.)
 - A Fir 65" dia., bears S.40½°W., 93 lks. dist., with healed blaze.
 - A Fir 48" dia., bears N.43¼°W., 50 lks. dist., with scribe marks T26S R9 S BT visible on weathered bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 12" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T26-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 26 S
R 9 W R 8 W
S 24 S 19
S 25 S 30
1967

from which a new bearing tree
A Fir 65" dia., bears N.16°E., 9 lks. dist. mkd. T26S R8W
S19 BT.

From this point United States Coast and Geodetic Survey
triangulation station ELWOODS 1953, bears S.67°51'E., 18.61
chs. dist., monumented with a standard brass cap, 3½" dia.,
firmly set in a concrete post, 10" dia., extending 8" above
ground, with top marked ELWOODS 1973, and a triangle.