

TOWNSHIP 26 RANGE 09 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7, T26-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4645)

Set ¼ post, 3 ft. long, 3" sq., from which
A Maple 24" dia., bears S.60°W., 40 lks. dist.
A Maple 30" dia., bears S.85°E., 45 lks. dist.

GLO resurvey by John W. Meldrum, Deputy Surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4724-25)

Set Cedar post 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S. on W. face, from which
A Hemlock 9" dia., bears S.89°30'E., 144 lks. dist. mkd. ¼ S BT.
A Maple 18" dia., bears N.28°45'E., 69 lks. dist., mkd. ¼ S BT.

From this corner, the old ¼ sec. cor. which was a post, now rotted away, or otherwise destroyed. The cor. point being witnessed as described by the Surveyor General, bears S.13°45'E., 232 lks. dist., I obliterate the marks on the old bearing trees.

Survey by Robert C. Adamek - For: Weyerhaeuser Co. - Sept. 23, 1974 - C.S. File 58/23 and M 54-75

No trace of orig. BTs was found. The correct position was determined by single proportion & fell in Cedar Creek, so a: 1" Iron Pipe WITNESS CORNER was established, N.28°36.5'W., 18.11 ft. to the true position.
The witness corner was referenced as follows:
Large boulder bears N.73°51.5'E., 11.4 ft.
24" Alder, bears S.78°31.5'W., 38.3 ft.