

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. S. 31; & (SE Cor. S. 36, T27-1)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #473, dated June 5, 1883
-(DCSO records Vol. 11 Page(s) 4771-72)

Set post 48x4 ins. firmly in the ground for stan. cor. to
Tps. 27 S., Rs. 1 W. and 1 E. marked S C T27S on N.; R1E S31
on E.; and R1W S36 on W. faces, 6 notches on N., E., and W.,
from which

- A Laurel 8" dia., bears N.25°E., 26 lks. dist. mkd. T27S
R1E S31 BT.
- A Fir 24" dia., bears N.50°W., 194 lks. dist. mkd. T27S
R1W S36 BT.
- A Laurel 10" dia., bears S.35°W., 25 lks. dist. mkd. S BT.

GLO resurvey by Homer D. Angell, Deputy Surveyor, under
contract #747, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4771)

Set post 48x4" firmly in the ground for stan. cor. to Tps. 27
S, Rs. 1W & 1E mkd S C T 27 S on N, R 1 E S31 on E and R 1 W
S 36 on W faces - 6 notches on N, E, & W, from which

- A laurel 8" dia., bears N.25°E. 26 lks mkd T27S R1E S31 BT

GLO resurvey by Lincoln E. Wilkes, U.S. Cadastral Engineer;
Otto L. Draper, U.S. Transitman & Norman D. Price, U.S.
Transitman, under Special Instructions, dated Dec. 21, 1920
-(DCSO records Vol. 24 Page(s) 10261)

The standard cor. of Tps. 27 S., Rs. 1E and 1W. is a badly
decayed Fir post, 4" sq., 18" above ground, loosely set,
markings almost obliterated; from which

- A Laurel stump 8" dia., bears N.25°E., 26 lks. dist. no
markings distinguishable.
- A Laurel stump 10" dia., bears S.35°W., 25 lks. dist., no
marks distinguishable.

Find no evidence of bearing tree described as a Fir 24"
dia., bearing N.50°W., 194 lks. mkd. T27S R1W S36 BT.
Two bark scribed BTs not described in the original field
notes were found as follows:

- A Fir 7" dia., bears N.40°E., 30 lks. dist. mkd. T27S R1E
S31 BT.
- A Fir 26" dia., bears N.40°W., 22 lks. dist. mkd. T27S R1W
S36 BT.

In place of badly decayed post, SET an Iron post 3 ft. long,
3" dia., 27" in the ground for standard cor., with brass cap
marked (Cont. Next Page)

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. S. 31; & (SE Cor. S. 36, T27-1)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

SC
T27S
R1W|R1E
S36|S31
1927

I blaze and mark new BTs as follows:
A Fir 7" dia., bears N.40°E., 30 lks. dist. mkd. T27S R1E
S31 SC BT,
A Fir 26" dia., bears N.40°W., 22 lks. dist. mkd. T27S R1W
S36 SC BT.