

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4793) and dupl. Pg. #9831-32, Vol. 23)

Set a basalt stone 15x10x5 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 18" dia., bears S.85°E., 37 lks. dist. mkd. ¼ S31 BT
A Fir 16" dia., bears N.72½°W., 28 lks. dist. mkd. ¼ S36 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9840-41)

The ¼ sec. cor. established for secs. 31 and 36, which is a basalt stone 10x5x7 ins., above ground, marked ¼ on W. face. Alongside of old stone cor.
Set an Iron post 3 ft. long, 1" dia., 27" in ground for the ¼ sec. cor. with brass cap mkd. ¼
S36 | S31
1928

from which
A Fir 20" dia., bears S.85°E., 37 lks. dist. mkd. ¼ S31 BT. (Old BT)
A Fir 18" dia., bears N.72½°W., 28 lks. dist. mkd. ¼ S36 BT. (Old BT.)

Fd. stone and 2 BTs. Did not find 1928 brass cap - Bruce Shaner, Dec. 1965 - C.S. File 51/332