

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100239

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only; T27-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4794) and (Dup. Pg. 9833, Vol. 23)

-----  
Set a basalt stone 15x10x6 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Cedar 18" dia., bears N.12°E., 31 lks. dist. mkd. ¼ S30 BT.  
A Hemlock 12" dia., bears N.70°W., 12 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9842-43)

-----  
Intersect the original ¼ sec.cor. established for secs. 25 and 30, which is a basalt stone 12x6x10 ins. above ground, marked ¼ on W. face. I change this cor. to refer to sec. 25 only, obliterating the marks on the old NE. BT.  
Alongside the old stone cor.:  
Set an Iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 25 only, with brass cap mkd.  
¼ S 25|  
1927

from which  
A Cedar 20" dia., bears N.12°E., 31 lks. dist. mkd. ¼ S30 BT. (Old BT)  
A Hemlock 16" dia., bears N.70°W., 12 lks. dist. mkd. ¼ S25 BT (Old BT)  
A Cedar 8" dia., bears S.16°W., 54 lks. dist. mkd. ¼ S25 BT.