

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only; T27-1W

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4796) and (Dup. Pg. 9834, Vol. 23)

-----  
A basalt stone 15x12x10 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 18" dia., bears S.61°E., 30 lks. dist. mkd. ¼ S19 BT.  
A Fir 24" dia., bears N.59°W., 22 lks. dist. mkd. ¼ S24 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9844-45)

-----  
Intersect the old ¼ sec. cor. established for secs. 19 & 24, which is a basalt stone 9x6x10 ins. above ground, marked ¼ on W. face. I change this cor. to refer to sec. 24 only, destroying the old scribe marks in the SE. bearing tree. Alongside of old stone cor. ;  
Set an iron post 3 ft. long, 1" in dia., 27" in the ground, for the ¼ sec. cor. of sec. 24 only, with brass cap marked:  
¼ S24 |  
1927

from which  
A Fir 22" dia., bears S.61°E., 30 lks. dist. mkd. ¼ S19 BT. (Old BT)  
A Fir 30" dia., bears N.59°W., 22 ks. dist. mkd. ¼ S24 BT. (Old BT)  
A Fir 32" dia., bears S.40°W., 40 lks. dist. mkd. ¼ S24 BT. (Old BT)

Survey by Burton W. Holt - Wit: Jim Coon - Dec. 3, 1960 - C.S. File 51/100-2

-----  
As determined by old BTs:  
32" Fir S.40°W., 26.4 ft., scribes and tree in good condition.  
The 30" Fir, N.59°W., 14.5 ft. was removed in road construction.  
22" Fir, S.61°E., 19.8 ft., new stump with face where scribes were purposely destroyed.  
Line tree 13.2 ft. North.  
Old stone mkd. ¼ but the brass cap and pipe are missing.  
Set 1/2" x 36" Iron rod with 1" sq. nut at top for corner and set new BT, which is (Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

46" D.Fir bears S.72°W., 29.8 ft. to face of tree, mkd. ¼  
S24 BT on bark.  
This corner is approx. 80 ft. South of the Cloburn Sale Road  
and 50 ft. S. of W. 1/4 Cor. sec. 19, T27S R1E.

Douglas Co. Surveyors Office - John M. Powell, and crew -  
Oct. 22, 1969 - C.S. File 54/94-6

-----  
Found - 1" Iron bolt at ¼ corner.  
Orig. 22" D.Fir now out of ground, S.61°E., 19.8  
ft., tree on face.  
Orig. 30" D.Fir, now stump out of ground, N.59°W.,  
14.5 ft. scribe visible.  
Orig. 32" now 34" D.Fir S.40°W., 26.4 ft. tree  
opened, scribe visible. Ring count in correct to  
face.  
42" D.Fir S.72°W., 29.8 ft. (face) bark scribed "¼  
S24 BT"

No trace of 1927 GL0 brass cap.  
Set Brass cap at cor. mkd: County Surveyors Office  
R T 27 S R  
1 ¼ S 24 | 1  
W | E  
1969

Reblazed and rescribed:  
42" D.Fir S.72°W., 31.6 ft.  
Original distance between corner of 19 & 24 is 88.4 ft. I  
find it 46.0 ft.