

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only (East) T27-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4796) and (Dup. Pgs. 9834-35, Vol. 23)

Set a basalt stone 15x8x8 ins., 10" in ground for cor. of secs. 13, 18, 19 and 24, marked with 3 notches on N. and S. sides, from which

- A Yew 10" dia., bears N.47½°E., 20 lks. dist. mkd. T27S R1E S18 BT.
- A Fir 30" dia., bears S.6°E., 19 lks. dist. mkd. T27S R1E S19 BT.
- A Fir 30" dia., bears S.37°W., 60 lks. dist. mkd. T27S R1W S24 BT.
- A Fir 24" dia., bears N.74°W., 25 lks. dist. mkd. T27S R1W S13 BT.

GL0 resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9845-46)

Intersect the old cor. established for secs. 13, 18, 19 and 24, which is a basalt stone 8x8x10 ins. above ground, marked with 3 notches on the N. and 3 notches on the S. edges. I change this cor. to refer to secs. 13 & 24 only, obliterating the old scribe marks on the NE. and SE. bearing tree.

Alongside of old stone cor.;

Set an iron post 3 ft. long, 2" dia., 27" in the ground, for the cor. of secs. 13 & 24 only, with brass cap marked:

T27S		T27S
S13		S 19
S24		
R1W		R1E
1927		

from which

- A Yew 12" dia., bears N.47½°E., 20 lks. dist. mkd. T27S R1E S18 BT (Old BT)
- A Fir 34" dia., bears S.6°E., 19 lks. dit. mkd. T27S R1E S19 BT. (Old BT)
- A Fir 34" dia., bears S.37°W., 60 lks. dist. mkd. T27S R1W S24 BT. (Old BT)
- A Fir 30" dia., bears N.74°W., 25 lks. dist. mkd. T27S R1W S13 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 27, 1969 - C.S. File 54/94-8

Found - Orig. 30" now 36" D.Fir N.74°W., 16.5 ft. opened for scribe. (Cont. Next Page)

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100378

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only (East) T27-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 34" now 39" D.Fir S.37°W., 39.6 ft., shows good scar.
No trace of 1927 GLO brass cap as cor. lies on very steep, NW. slope, very rocky, probably slid out.
Set Brass cap at cor. mkd: County Surveyors Office
R T 27 S R
1 S 13 | S 19 1
W S 24 | E
1969
Bearing trees OK and tagged.