

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100438

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only: T27-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4797) and (Dup. Pg. 9835, Vol. 23)

Set basalt stone 15x10x8 ins., 10" in ground for 1/4 sec. cor. marked 1/4 on W. face, from which
A Fir 24" dia., bears S.70°E., 30 lks. dist. mkd. 1/4 S18 BT.
A Fir 10" dia., bears S.15°W., 34 lks. dist. mkd. 1/4 S13 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9846-47)

Intersect the old 1/4 sec. cor. established for secs. 13 & 18, which is a basalt stone 10x8x7 ins. above ground, marked 1/4 on the W. face.
I change this cor. to refer to sec. 13 only, obliterating the old scribe marks on the SE. bearing tree.
Alongside of old cor. stone;
Set an iron post 3 ft. long, 1" dia., 27" in the ground for the 1/4 sec. cor. of sec. 13 only, with brass cap marked:
1/4 S13 |
1927

from which
A Fir 28" dia., bears S.70°E., 30 lks. dist. mkd. 1/4 S18 BT. (Old BT)
A Fir 14" dia., bears S.15°W., 38 lks. dist. mkd. 1/4 S13 BT. (Old BT)
A Fir 14" dia., bears N.79°W., 44 lks. dist. mkd. 1/4 S13 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 8, 1969 - C.S. File 54/94-77

Found - 10x8x7 stone, firmly set, however, mkd. "1/4" on East side.
Orig. 14" now 27" D.Fir, S.15°W., (Orig. 22.4 ft.) (1927, 25.1 ft.), shows good scar. (Orig. tree destroyed)
28" Fir now stump, S.70°E., 19.8 ft.
14" now 19" D.Fir N.86°W., (Rec. N.79°W.) 29.0 ft., opened for scribe.

Set Brass cap at cor. mkd: County Surveyors Office
R T 27 S R
1 1/4 S 13 | 1
W 1969 E

(Cont. Next Page)

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100438

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only: T27-1W

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Reblazed and rescribed:

27" D.Fir S.15°W., 22.4 ft. mkd. "¼ S13 CS BT".

This corner lies 119.0 ft. So. of ¼ cor. Sec. 18, T27-1E.
(Rec. 116.2 ft.)