

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13 only (East) T27-1W

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4797) and (Dup. Pg. 9836, Vol. 23)

 Set a basalt stone 20x10x4 ins., 15" in ground for cor. of secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edges, from which

- A Cedar 12" dia., bears N.30°E., 29 lks. dist. mkd. T27S R1E S7 BT.
- A Fir 12" dia., bears S.65°E., 35 lks. dist. mkd. T27S R1E S18 BT.
- A Yew 10" dia., bears S.61½°W., 43 lks. dist. mkd. T27S R1W S13 BT.
- A Dogwood 10" dia., bears N.28°W., 23 lks. dist. mkd. T27S R1W S12 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9847-48)

 Intersect the old cor. established for secs. 7, 12, 13 and 18, which is a basalt stone 14x4x8 ins. above ground, marked with 2 notches on the N. and 4 notches on the S. edges.

I change this cor. to refer to secs. 12 and 13 only, obliterating the old scribe marks on the old NE. and SE. bearing trees. Alongside of old cor. stone, Set an Iron post 3 ft. long, 2" dia., 27" in the ground, for the cor. of secs. 12 & 13 only, with brass cap marked:

T27S	T27S
S 12	S 18
S 13	
R1W	R1E
1927	

from which

- A Cedar 16" dia., bears N.30°E., 29 lks. dist. mkd. T27S R1E S7 BT. (Old BT)
- A Fir 16" dia., bears S.65°E., 35 lks. dist. mkd. T27S R1E S18 BT. (Old BT)
- A Yew 12" dia., bears S.61½°W., 43 lks. dist. mkd. T27S R1W S13 BT. (Old BT)
- A Dogwood 12" dia., bears N.28°W., 23 lks. dist. mkd. T27S R1W S12 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 8, 1969 - C.S. File 54/94-78

 Found - 20x10x4 stone, firmly set, mkd. 2 notches N. and 4, South. (Cont. Next Page)

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100477

PRIMARY CORNER DESCRIPTION Sec Cor. for 12 & 13 only (East) T27-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

No trace of brass cap being set.
No trace of NW. or NE. BTs.
Orig. 16" Fir, S.65°E., 23.1 ft., this tree
destroyed.
12" now 16" Yew, S.61½°W., 43.4 ft. (Rec. 28.4 ft.),
scribe visible. Reblazed and rescribed "T27S R1W
S12 CS BT".

Set Brass cap at cor. mkd: County Surveyors Office
R T 27 S R
1 S 12 | S 18 1
W S 13 | E
1969

New BT - 30" D.Fir N.9°W., 25.1 ft. mkd. T27S R1W S12 CS BT.